

OPM 5278

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

Form Approved
OMB No. 44-R1387

MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing,
Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

CALLA CHEMICAL COMPANY A DIV. SECTION I	
MANUFACTURER'S NAME DIVERSIFIED CHEMICALS CORP.	EMERGENCY TELEPHONE NO. 714-828-4470
ADDRESS (Number, Street, City, State, and ZIP Code) 8100 ELECTRIC AVE., STANTON CALIFORNIA 90680	
CHEMICAL NAME AND SYNONYMS SURFACTANT BLEND	TRADE NAME AND SYNONYMS CALLA 301A
CHEMICAL FAMILY	FORMULA

SECTION II - HAZARDOUS INGREDIENTS					
PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS			BASE METAL		
CATALYST			ALLOYS		
VEHICLE			METALLIC COATINGS		
SOLVENTS			FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS		
OTHERS					
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES				%	TLV (Units)

SECTION III - PHYSICAL DATA			
BOILING POINT (°F.)	211	SPECIFIC GRAVITY (H ₂ O=1)	108
VAPOR PRESSURE (mm Hg.) 20° C	17.5	PERCENT. VOLATILE BY VOLUME (%)	
VAPOR DENSITY (AIR=1)		EVAPORATION RATE (_____ =1)	
SOLUBILITY IN WATER			
APPEARANCE AND ODOR			

SECTION IV - FIRE AND EXPLOSION HAZARD DATA			
FLASH POINT (Method used)	None to Boiling	FLAMMABLE LIMITS	LeI UeI
EXTINGUISHING MEDIA	Water		
SPECIAL FIRE FIGHTING PROCEDURES	None		
UNUSUAL FIRE AND EXPLOSION HAZARDS			
None			